



Yilai Power Technology Co, Ltd

Tel:+86-755-2930 0814 Web:yilaipower.com Email:info@yilaipower.com

Li-ion Polymer Series

Model	Nominal Capacity (mAh)	Nominal Voltage (V)	Max Dimension(mm)		
			Thickness	Width	Length
251175	170	3.7	2.5	11.5	75.5
251328	65	3.7	2.5	13.5	28.5
251730	90	3.7	2.5	17.5	30.5
252030	100	3.7	2.5	20.5	30.5
301020	40	3.7	3.0	10.5	20.5
301221	60	3.7	3.0	12.5	21.5
301525	80	3.7	3.0	15.5	25.5
301745	180	3.7	3.0	17.5	47.5
301925	130	3.7	3.0	19.5	25.5
302030	130	3.7	3.0	20.5	30.5
302035	180	3.7	3.0	20.5	35.5
302250	300	3.7	3.0	22.5	50.5
302260	400	3.7	3.0	22.5	62.5
302530	200	3.7	3.0	25.5	32.5
302550	410	3.7	3.0	25.5	52.5
303030	210	3.7	3.0	30.5	32.5
303035	300	3.7	3.0	30.5	37.5
303060	600	3.7	3.0	30.5	60.5
303449	500	3.7	3.0	34.5	51.5
304050	700	3.7	3.0	40.5	50.5
304548	620	3.7	3.0	45.5	48.5
312050	300	3.7	3.1	20.5	50.5
322430	200	3.7	3.2	24.5	32.5
333040	300	3.7	3.3	30.5	42.5
351525	100	3.7	3.5	15.5	27.5
351638	200	3.7	3.5	16.5	38.5
352033	190	3.7	3.5	20.5	33.5
352424	200	3.7	3.5	24.5	24.5
353046	480	3.7	3.5	30.5	46.5
353450	650	3.7	3.5	34.5	50.5
354048	480	3.7	3.5	40.5	48.5
354448	800	3.7	3.5	44.5	48.5
355060	1000	3.7	3.5	50.5	60.5
365063	1200	3.7	3.6	50.5	63.5
373040	450	3.7	3.7	30.5	42.5



Yilai Power Technology Co, Ltd

Tel:+86-755-2930 0814 Web:yilaipower.com Email:info@yilaipower.com

Li-ion Polymer Series

Model	Nominal Capacity (mAh)	Nominal Voltage (V)	Max Dimension(mm)		
			Thickness	Width	Length
381434	160	3.7	3.8	14.5	34.5
382030	190	3.7	3.8	20.5	30.5
382427	210	3.7	3.8	24.5	29.5
382530	210	3.7	3.8	25.5	30.5
383030	320	3.7	3.8	30.5	32.5
383040	450	3.7	3.8	30.5	42.5
383450	650	3.7	3.8	34.5	50.5
401020	60	3.7	4.0	10.5	20.5
401027	80	3.7	4.0	10.5	27.5
401225	100	3.7	4.0	12.5	25.5
401230	120	3.7	4.0	12.5	32.5
401425	110	3.7	4.0	14.5	25.5
401434	160	3.7	4.0	14.5	34.5
401535	200	3.7	4.0	15.5	35.5
401540	240	3.7	4.0	15.5	42.5
401550	300	3.7	4.0	15.5	50.5
402020	120	3.7	4.0	20.5	20.5
402025	150	3.7	4.0	20.5	27.5
402030	180	3.7	4.0	20.5	32.5
402030	200	3.7	4.0	20.5	32.5
402035	240	3.7	4.0	20.5	37.5
402035	250	3.7	4.0	20.5	37.5
402040	300	3.7	4.0	20.5	42.5
402040	320	3.7	4.0	20.5	40.5
402049	400	3.7	4.0	20.5	51.5
402060	500	3.7	4.0	20.5	62.5
402248	400	3.7	4.0	22.5	50.5
402525	250	3.7	4.0	25.5	27.5
402530	300	3.7	4.0	25.5	32.5
402535	310	3.7	4.0	25.5	37.5
402535	320	3.7	4.0	25.5	37.5
402540	430	3.7	4.0	25.5	40.5
402545	450	3.7	4.0	25.5	45.5
402560	600	3.7	4.0	25.5	62.5
403030	300	3.7	4.0	30.5	32.5



Yilai Power Technology Co, Ltd

Tel:+86-755-2930 0814 Web:yilaipower.com Email:info@yilaipower.com

Li-ion Polymer Series

Model	Nominal Capacity (mAh)	Nominal Voltage (V)	Max Dimension(mm)		
			Thickness	Width	Length
403030	310	3.7	4.0	30.5	32.5
403035	400	3.7	4.0	30.5	37.5
403035	420	3.7	4.0	30.5	37.5
403040	380	3.7	4.0	30.5	42.5
403040	390	3.7	4.0	30.5	42.5
403040	400	3.7	4.0	30.5	42.5
403040	450	3.7	4.0	30.5	42.5
403435	450	3.7	4.0	34.5	37.5
403450	800	3.7	4.0	34.5	50.5
412223	200	3.7	4.1	22.5	23.5
412856	720	3.7	4.1	28.5	56.5
421233	125	3.7	4.2	12.5	33.5
421920	120	3.7	4.2	19.5	20.5
422123	200	3.7	4.2	21.5	23.5
423034	400	3.7	4.2	30.5	34.5
423040	520	3.7	4.2	30.5	42.5
423450	800	3.7	4.2	34.5	50.5
431730	200	3.7	4.3	17.5	30.5
433040	530	3.7	4.3	30.5	42.5
433950	1000	3.7	4.3	39.5	50.5
442530	300	3.7	4.4	25.5	30.5
451624	150	3.7	4.5	16.5	24.5
451826	200	3.7	4.5	18.5	28.5
452025	150	3.7	4.5	20.5	25.5
452030	250	3.7	4.5	20.5	30.5
452035	300	3.7	4.5	20.5	35.5
452535	350	3.7	4.5	25.5	37.5
453038	500	3.7	4.5	30.5	38.5
454070	1200	3.7	4.5	40.5	70.5
464948	1350	3.7	4.6	49.5	48.5
481530	180	3.7	4.8	15.5	30.5
492728	350	3.7	4.9	27.5	28.5
501035	150	3.7	5.0	10.5	37.5
501225	120	3.7	5.0	12.5	27.5
501230	150	3.7	5.0	12.5	30.5



Yilai Power Technology Co, Ltd

Tel:+86-755-2930 0814 Web:yilaipower.com Email:info@yilaipower.com

Li-ion Polymer Series

Model	Nominal Capacity (mAh)	Nominal Voltage (V)	Max Dimension(mm)		
			Thickness	Width	Length
501240	200	3.7	5.0	12.5	42.5
501420	95	3.7	5.0	14.5	20.5
501430	180	3.7	5.0	14.5	32.5
501440	280	3.7	5.0	14.5	42.5
501440	300	3.7	5.0	14.5	42.5
501447	280	3.7	5.0	14.5	47.5
501525	180	3.7	5.0	15.5	27.5
501530	200	3.7	5.0	15.5	32.5
501535	240	3.7	5.0	15.5	35.5
501645	380	3.7	5.0	16.5	47.5
501646	360	3.7	5.0	16.5	48.5
501725	235	3.7	5.0	17.5	25.5
501726	220	3.7	5.0	17.5	28.5
501730	200	3.7	5.0	17.5	32.5
501818	120	3.7	5.0	18.5	18.5
501930	200	3.7	5.0	19.5	32.5
502020	150	3.7	5.0	20.5	20.5
502023	200	3.7	5.0	20.5	23.5
502025	240	3.7	5.0	20.5	27.5
502029	250	3.7	5.0	20.5	29.5
502029	260	3.7	5.0	20.5	29.5
502030	200	3.7	5.0	20.5	32.5
502030	250	3.7	5.0	20.5	32.5
502035	300	3.7	5.0	20.5	37.5
502040	400	3.7	5.0	20.5	42.5
502045	450	3.7	5.0	20.5	45.5
502050	500	3.7	5.0	20.5	52.5
502248	500	3.7	5.0	22.5	50.5
502248	520	3.7	5.0	22.5	48.5
502440	450	3.7	5.0	24.5	40.5
502530	300	3.7	5.0	25.5	32.5
502535	400	3.7	5.0	25.5	37.5
502535	450	3.7	5.0	25.5	37.5
502540	500	3.7	5.0	25.5	42.5
503030	400	3.7	5.0	30.5	32.5



Yilai Power Technology Co, Ltd

Tel:+86-755-2930 0814 Web:yilaipower.com Email:info@yilaipower.com

Li-ion Polymer Series

Model	Nominal Capacity (mAh)	Nominal Voltage (V)	Max Dimension(mm)		
			Thickness	Width	Length
503030	450	3.7	5.0	30.5	32.5
503035	500	3.7	5.0	30.5	37.5
503040	600	3.7	5.0	30.5	42.5
503048	750	3.7	5.0	30.5	50.5
503348	930	3.7	5.0	33.5	48.5
503450	1000	3.7	5.0	34.5	50.5
503759	1200	3.7	5.0	37.5	59.5
503942	950	3.7	5.0	39.5	42.5
512231	360	3.7	5.1	22.5	31.5
522027	260	3.7	5.2	20.5	27.5
523040	600	3.7	5.2	30.5	42.5
534347	1300	3.7	5.3	43.5	47.5
542427	400	3.7	5.4	24.5	27.5
542728	390	3.7	5.4	27.5	28.5
546065	2500	3.7	5.4	60.5	65.5
550940	160	3.7	5.5	9.5	42.5
551525	190	3.7	5.5	15.5	25.5
551535	240	3.7	5.5	15.5	35.5
551919	170	3.7	5.5	19.5	19.5
551965	800	3.7	5.5	19.5	65.5
552035	350	3.7	5.5	20.5	35.5
552040	450	3.7	5.5	20.5	42.5
552068	1020	3.7	5.5	20.5	68.5
552123	300	3.7	5.5	21.5	25.5
552330	400	3.7	5.5	23.5	30.5
553454	1050	3.7	5.5	34.5	54.5
554468	2200	3.7	5.5	44.5	68.5
562035	400	3.7	5.6	20.5	35.5
562527	280	3.7	5.6	25.5	27.5
572040	450	3.7	5.7	20.5	42.5
581621	150	3.7	5.8	16.5	21.5
582030	300	3.7	5.8	20.5	30.5
582055	750	3.7	5.8	20.5	55.5
582525	300	3.7	5.8	25.5	25.5
582527	350	3.7	5.8	25.5	27.5



Yilai Power Technology Co, Ltd

Tel:+86-755-2930 0814 Web:yilaipower.com Email:info@yilaipower.com

Li-ion Polymer Series

Model	Nominal Capacity (mAh)	Nominal Voltage (V)	Max Dimension(mm)		
			Thickness	Width	Length
582727	350	3.7	5.8	27.5	29.5
582727	400	3.7	5.8	27.5	29.5
582728	380	3.7	5.8	27.5	30.5
582728	400	3.7	5.8	27.5	30.5
582728	450	3.7	5.8	27.5	28.5
582728	480	3.7	5.8	27.5	30.5
601045	265	3.7	6.0	10.5	47.5
601225	130	3.7	6.0	12.5	25.5
601225	150	3.7	6.0	12.5	25.5
601230	180	3.7	6.0	12.5	32.5
601230	200	3.7	6.0	12.5	32.5
601435	240	3.7	6.0	14.5	37.5
601435	280	3.7	6.0	14.5	37.5
601435	300	3.7	6.0	14.5	37.5
601448	400	3.7	6.0	14.5	48.5
601525	180	3.7	6.0	15.5	27.5
601530	230	3.7	6.0	15.5	30.5
601530	250	3.7	6.0	15.5	32.5
601535	300	3.7	6.0	15.5	35.5
601550	500	3.7	6.0	15.5	52.5
601750	500	3.7	6.0	17.5	50.5
601827	280	3.7	6.0	18.5	27.5
601919	170	3.7	6.0	19.5	19.5
602020	200	3.7	6.0	20.5	20.5
602025	250	3.7	6.0	20.5	27.5
602028	300	3.7	6.0	20.5	30.5
602030	320	3.7	6.0	20.5	32.5
602035	400	3.7	6.0	20.5	37.5
602040	450	3.7	6.0	20.5	42.5
602045	500	3.7	6.0	20.5	47.5
602050	600	3.7	6.0	20.5	52.5
602248	600	3.7	6.0	22.5	50.5
602248	650	3.7	6.0	22.5	50.5
602530	400	3.7	6.0	25.5	32.5
602535	480	3.7	6.0	25.5	37.5



Yilai Power Technology Co, Ltd

Tel:+86-755-2930 0814 Web:yilaipower.com Email:info@yilaipower.com

Li-ion Polymer Series

Model	Nominal Capacity (mAh)	Nominal Voltage (V)	Max Dimension(mm)		
			Thickness	Width	Length
602535	500	3.7	6.0	25.5	37.5
602540	600	3.7	6.0	25.5	42.5
602540	620	3.7	6.0	25.5	42.5
602540	650	3.7	6.0	25.5	42.5
603030	500	3.7	6.0	30.5	32.5
603030	520	3.7	6.0	30.5	32.5
603030	600	3.7	6.0	30.5	32.5
603035	620	3.7	6.0	30.5	37.5
603040	600	3.7	6.0	30.5	42.5
603040	650	3.7	6.0	30.5	42.5
603040	750	3.7	6.0	30.5	42.5
603046	800	3.7	6.0	30.5	48.5
603048	900	3.7	6.0	30.5	50.5
603055	1000	3.7	6.0	30.5	55.5
603449	1100	3.7	6.0	34.5	49.5
604347	1500	3.7	6.0	43.5	47.5
604550	1550	3.7	6.0	45.5	50.5
621525	220	3.7	6.2	15.5	27.5
651248	330	3.7	6.5	12.5	48.5
651432	280	3.7	6.5	14.5	32.5
651860	800	3.7	6.5	18.5	60.5
652025	300	3.7	6.5	20.5	25.5
652530	500	3.7	6.5	25.5	30.5
652728	500	3.7	6.5	27.5	28.5
653636	900	3.7	6.5	36.5	36.5
671818	160	3.7	6.7	18.5	18.5
681345	400	3.7	6.8	13.5	47.5
682028	380	3.7	6.8	20.5	28.5
682030	400	3.7	6.8	20.5	32.5
701225	160	3.7	7.0	12.5	27.5
701230	230	3.7	7.0	12.5	32.5
701230	250	3.7	7.0	12.5	32.5
701240	280	3.7	7.0	12.5	42.5
701250	400	3.7	7.0	12.5	52.5
701250	430	3.7	7.0	12.5	52.5



Yilai Power Technology Co, Ltd

Tel:+86-755-2930 0814 Web:yilaipower.com Email:info@yilaipower.com

Li-ion Polymer Series

Model	Nominal Capacity (mAh)	Nominal Voltage (V)	Max Dimension(mm)		
			Thickness	Width	Length
701345	400	3.7	7.0	13.5	47.5
701435	300	3.7	7.0	14.5	37.5
701435	320	3.7	7.0	14.5	37.5
701530	300	3.7	7.0	15.5	32.5
701535	320	3.7	7.0	15.5	37.5
701717	130	3.7	7.0	17.5	17.5
701732	330	3.7	7.0	17.5	32.5
701734	350	3.7	7.0	17.5	34.5
701735	330	3.7	7.0	17.5	35.5
701831	350	3.7	7.0	18.5	31.5
701849	650	3.7	7.0	18.5	49.5
702020	200	3.7	7.0	20.5	20.5
702024	300	3.7	7.0	20.5	24.5
702028	330	3.7	7.0	20.5	28.5
702030	400	3.7	7.0	20.5	32.5
702035	450	3.7	7.0	20.5	37.5
702035	480	3.7	7.0	20.5	37.5
702040	500	3.7	7.0	20.5	42.5
702045	600	3.7	7.0	20.5	47.5
702050	800	3.7	7.0	20.5	52.5
702325	350	3.7	7.0	23.5	27.5
702425	400	3.7	7.0	24.5	27.5
702530	500	3.7	7.0	25.5	32.5
702535	600	3.7	7.0	25.5	37.5
702728	480	3.7	7.0	27.5	28.5
703030	650	3.7	7.0	30.5	30.5
703035	700	3.7	7.0	30.5	35.5
703048	1130	3.7	7.0	30.5	48.5
704070	2500	3.7	7.0	40.5	70.5
731230	250	3.7	7.3	12.5	32.5
731727	350	3.7	7.3	17.5	29.5
732828	550	3.7	7.3	28.5	30.5
742535	700	3.7	7.4	25.5	35.5
751425	230	3.7	7.5	14.5	27.5
751524	230	3.7	7.5	15.5	26.5



Yilai Power Technology Co, Ltd

Tel:+86-755-2930 0814 Web:yilaipower.com Email:info@yilaipower.com

Li-ion Polymer Series

Model	Nominal Capacity (mAh)	Nominal Voltage (V)	Max Dimension(mm)		
			Thickness	Width	Length
751524	240	3.7	7.5	15.5	26.5
751525	230	3.7	7.5	15.5	27.5
751525	250	3.7	7.5	15.5	27.5
751535	350	3.7	7.5	15.5	37.5
751535	380	3.7	7.5	15.5	37.5
751535	400	3.7	7.5	15.5	37.5
752035	500	3.7	7.5	20.5	35.5
753035	800	3.7	7.5	30.5	37.5
781548	500	3.7	7.8	15.5	48.5
801340	350	3.7	8.0	13.5	42.5
801350	500	3.7	8.0	13.5	52.5
801426	260	3.7	8.0	14.5	28.5
801429	300	3.7	8.0	14.5	31.5
801435	400	3.7	8.0	14.5	37.5
801437	350	3.7	8.0	14.5	37.5
801437	370	3.7	8.0	14.5	37.5
801520	200	3.7	8.0	15.5	20.5
801523	260	3.7	8.0	15.5	23.5
801525	240	3.7	8.0	15.5	25.5
801525	250	3.7	8.0	15.5	25.5
801529	300	3.7	8.0	15.5	29.5
801535	400	3.7	8.0	15.5	37.5
801640	500	3.7	8.0	16.5	40.5
801723	230	3.7	8.0	17.5	23.5
801737	480	3.7	8.0	17.5	39.5
801738	500	3.7	8.0	17.5	40.5
801740	550	3.7	8.0	17.5	40.5
801750	700	3.7	8.0	17.5	50.5
801829	300	3.7	8.0	18.5	29.5
801837	500	3.7	8.0	18.5	39.5
802020	240	3.7	8.0	20.5	20.5
802022	300	3.7	8.0	20.5	22.5
802025	350	3.7	8.0	20.5	27.5
802030	400	3.7	8.0	20.5	32.5
802030	450	3.7	8.0	20.5	32.5



Yilai Power Technology Co, Ltd

Tel:+86-755-2930 0814 Web:yilaipower.com Email:info@yilaipower.com

Li-ion Polymer Series

Model	Nominal Capacity (mAh)	Nominal Voltage (V)	Max Dimension(mm)		
			Thickness	Width	Length
802035	500	3.7	8.0	20.5	37.5
802035	520	3.7	8.0	20.5	35.5
802040	600	3.7	8.0	20.5	42.5
802040	650	3.7	8.0	20.5	42.5
802045	750	3.7	8.0	20.5	47.5
802050	800	3.7	8.0	20.5	52.5
802070	1000	3.7	8.0	20.5	70.5
802350	1050	3.7	8.0	23.5	50.5
802526	400	3.7	8.0	25.5	26.5
802530	600	3.7	8.0	25.5	32.5
802535	700	3.7	8.0	25.5	37.5
802535	750	3.7	8.0	25.5	37.5
802540	800	3.7	8.0	25.5	42.5
802632	700	3.7	8.0	26.5	32.5
803030	700	3.7	8.0	30.5	32.5
803030	740	3.7	8.0	30.5	30.5
803035	800	3.7	8.0	30.5	37.5
803040	1000	3.7	8.0	30.5	42.5
803450	1000	3.7	8.0	34.5	52.5
803535	1000	3.7	8.0	35.5	35.5
831445	500	3.7	8.3	14.5	47.5
831550	600	3.7	8.3	15.5	52.5
832935	1000	3.7	8.3	29.5	37.5
851550	680	3.7	8.5	15.5	52.5
851730	400	3.7	8.5	17.5	32.5
852024	350	3.7	8.5	20.5	24.5
852025	390	3.7	8.5	20.5	27.5
852040	650	3.7	8.5	20.5	40.5
852055	1000	3.7	8.5	20.5	55.5
882574	2300	3.7	8.8	25.5	74.5
883030	820	3.7	8.8	30.5	30.5
901430	360	3.7	9.0	14.5	32.5
901525	300	3.7	9.0	15.5	27.5
901538	500	3.7	9.0	15.5	40.5
901635	470	3.7	9.0	16.5	35.5



Yilai Power Technology Co, Ltd

Tel:+86-755-2930 0814 Web:yilaipower.com Email:info@yilaipower.com

Li-ion Polymer Series

Model	Nominal Capacity (mAh)	Nominal Voltage (V)	Max Dimension(mm)		
			Thickness	Width	Length
901752	800	3.7	9.0	17.5	52.5
902025	400	3.7	9.0	20.5	27.5
902030	500	3.7	9.0	20.5	32.5
902035	600	3.7	9.0	20.5	37.5
902035	620	3.7	9.0	20.5	37.5
902035	650	3.7	9.0	20.5	37.5
902040	700	3.7	9.0	20.5	42.5
902050	800	3.7	9.0	20.5	50.5
902050	1000	3.7	9.0	20.5	50.5
902124	400	3.7	9.0	21.5	24.5
902523	400	3.7	9.0	25.5	23.5
902525	500	3.7	9.0	25.5	27.5
902528	550	3.7	9.0	25.5	28.5
902530	650	3.7	9.0	25.5	30.5
902535	800	3.7	9.0	25.5	37.5
902535	850	3.7	9.0	25.5	37.5
902554	1400	3.7	9.0	25.5	56.5
903035	1000	3.7	9.0	30.5	35.5
903040	1050	3.7	9.0	30.5	40.5
903448	1800	3.7	9.0	34.5	48.5
952045	900	3.7	9.5	20.5	45.5
952142	860	3.7	9.5	21.5	42.5
952540	850	3.7	9.5	25.5	40.5
973566	2700	3.7	9.7	35.5	66.5
101550	770	3.7	10.0	15.5	52.5
101550	800	3.7	10.0	15.5	52.5
102035	650	3.7	10.0	20.5	37.5
102040	800	3.7	10.0	20.5	42.5
102045	900	3.7	10.0	20.5	45.5
102050	1000	3.7	10.0	20.5	52.5
102057	1400	3.7	10.0	20.5	59.5
102530	700	3.7	10.0	25.5	32.5
102530	800	3.7	10.0	25.5	32.5
102539	1000	3.7	10.0	25.5	39.5
102550	1500	3.7	10.0	25.5	50.5



Yilai Power Technology Co, Ltd

Tel:+86-755-2930 0814 Web:yilaipower.com Email:info@yilaipower.com

Li-ion Polymer Series

Model	Nominal Capacity (mAh)	Nominal Voltage (V)	Max Dimension(mm)		
			Thickness	Width	Length
102830	850	3.7	10.0	28.5	30.5
103030	950	3.7	10.0	30.5	32.5
103080	3000	3.7	10.0	30.5	80.5
103449	2000	3.7	10.0	34.5	49.5
103450	1900	3.7	10.0	34.5	52.5
103763	2800	3.7	10.0	37.5	63.5
104050	2600	3.7	10.0	40.5	52.5
104065	3200	3.7	10.0	40.5	67.5
111840	650	3.7	11.0	18.5	40.5
112020	350	3.7	11.0	20.5	20.5
112045	950	3.7	11.0	20.5	45.5
112045	1000	3.7	11.0	20.5	45.5
112525	700	3.7	11.0	25.5	25.5
123040	1600	3.7	12.0	30.5	40.5
124050	3000	3.7	12.0	40.5	52.5
124065	4000	3.7	12.0	40.5	67.5
301324PL	70	3.7	3.0	13.5	24.5
301730PN	120	3.7	3.0	17.5	30.5
302025PN	110	3.7	3.0	20.5	25.5
302040PN	220	3.7	3.0	20.5	40.5
302323PN	110	3.7	3.0	23.5	23.5
302540PN	280	3.7	3.0	25.5	40.5
303450PN	500	3.7	3.0	34.5	50.5
304033PT	400	3.7	3.0	40.5	33.5
304048PN	600	3.7	3.0	40.5	48.5
304066PL	980	3.7	3.0	40.5	66.5
304380PN	1180	3.7	3.0	43.5	80.5
311020PL	40	3.7	3.1	10.5	20.5
312725PL	190	3.7	3.1	27.5	25.5
313342PN	480	3.7	3.1	33.5	42.5
321530PN	110	3.7	3.2	15.5	30.5
322728PN	250	3.7	3.2	27.5	28.5
341520PL	80	3.7	3.4	15.5	20.5
341723PL	120	3.7	3.4	17.5	23.5
351522PL	105	3.7	3.5	15.5	22.5



Yilai Power Technology Co, Ltd

Tel:+86-755-2930 0814 Web:yilaipower.com Email:info@yilaipower.com

Li-ion Polymer Series

Model	Nominal Capacity (mAh)	Nominal Voltage (V)	Max Dimension(mm)		
			Thickness	Width	Length
351828PN	140	3.7	3.5	18.5	28.5
352035PL	230	3.7	3.5	20.5	35.5
352067PN	450	3.7	3.5	20.5	67.5
352262PN	460	3.7	3.5	22.5	62.5
352327PN	200	3.7	3.5	23.5	27.5
353030PH	325	3.7	3.5	30.5	30.5
354578PL	1600	3.7	3.5	45.5	78.5
366076PL	2000	3.7	3.6	60.5	76.5
372532PN	280	3.7	3.7	25.5	32.5
382030PN	210	3.7	3.8	20.5	30.5
382427PN	220	3.7	3.8	24.5	27.5
391818PL	110	3.7	3.9	18.5	18.5
392072PL	660	3.7	3.9	20.5	72.5
393658PN	900	3.7	3.9	36.5	58.5
401220PN	70	3.7	4.0	12.5	20.5
401225PN	95	3.7	4.0	12.5	25.5
401230PN	120	3.7	4.0	12.5	30.5
401342PN	200	3.7	4.0	13.5	42.5
401523PL	120	3.7	4.0	15.5	23.5
401525PH	110	3.7	4.0	15.5	25.5
401525PN	120	3.7	4.0	15.5	25.5
402040PK	300	3.7	4.0	20.5	40.5
402040PN	330	3.7	4.0	20.5	40.5
402050PN	400	3.7	4.0	20.5	50.5
402226PH	220	3.7	4.0	22.5	26.5
402530PN	280	3.7	4.0	25.5	30.5
402561PN	700	3.7	4.0	25.5	62.5
403040PL	480	3.7	4.0	30.5	40.5
403048PH	600	3.7	4.0	30.5	48.5
404858PL	1380	3.7	4.0	48.5	58.5
412123PL	200	3.7	4.1	21.5	23.5
421535PN	200	3.7	4.2	15.5	35.5
423060PN	800	3.7	4.2	30.5	60.5
443758PL	1300	3.7	4.4	37.5	58.5
450943PN	160	3.7	4.5	9.5	43.5



Yilai Power Technology Co, Ltd

Tel:+86-755-2930 0814 Web:yilaipower.com Email:info@yilaipower.com

Li-ion Polymer Series

Model	Nominal Capacity (mAh)	Nominal Voltage (V)	Max Dimension(mm)		
			Thickness	Width	Length
451360PN	350	3.7	4.5	13.5	60.5
451535PH	200	3.7	4.5	15.5	35.5
452035PH	280	3.7	4.5	20.5	35.5
452067PL	700	3.7	4.5	20.5	67.5
452526PL	300	3.7	4.5	25.5	26.5
463126PL	420	3.7	4.6	31.5	26.5
473048PL	800	3.7	4.7	30.5	48.5
481220PL	90	3.7	4.8	12.5	20.5
481730PN	230	3.7	4.8	17.5	30.5
482831PN	440	3.7	4.8	28.5	31.5
492434PN	400	3.7	4.9	24.5	34.5
495060PL	2000	3.7	4.9	50.5	60.5
501228PH	150	3.7	5.0	12.5	28.5
501245PN	260	3.7	5.0	12.5	45.5
501520PN	125	3.7	5.0	15.5	20.5
501530PN	200	3.7	5.0	15.5	30.5
501621PN	130	3.7	5.0	16.5	21.5
501723PH	130	3.7	5.0	17.5	23.5
501735PN	300	3.7	5.0	17.5	35.5
501771PN	700	3.7	5.0	17.5	71.5
501865PN	600	3.7	5.0	18.5	65.5
502020PL	180	3.7	5.0	20.5	20.5
502030PK	280	3.7	5.0	20.5	30.5
502033PN	320	3.7	5.0	20.5	33.5
502040PN	400	3.7	5.0	20.5	40.5
502043PN	450	3.7	5.0	20.5	43.5
502065PN	700	3.7	5.0	20.5	65.5
502248PL	500	3.7	5.0	22.5	48.5
502260PH	600	3.7	5.0	22.5	60.5
502270PL	850	3.7	5.0	22.5	70.5
502270PN	900	3.7	5.0	22.5	70.5
502339PL	500	3.7	5.0	23.5	39.5
502525PN	300	3.7	5.0	25.5	25.5
502530PL	350	3.7	5.0	25.5	30.5
502535PN	450	3.7	5.0	25.5	35.5



Yilai Power Technology Co, Ltd

Tel:+86-755-2930 0814 Web:yilaipower.com Email:info@yilaipower.com

Li-ion Polymer Series

Model	Nominal Capacity (mAh)	Nominal Voltage (V)	Max Dimension(mm)		
			Thickness	Width	Length
502555PH	800	3.7	5.0	25.5	55.5
502832PN	450	3.7	5.0	28.5	32.5
503048PH	800	3.7	5.0	30.5	48.5
503080PH	1300	3.7	5.0	30.5	80.5
503450PH	1000	3.7	5.0	34.5	50.5
503942PN	930	3.7	5.0	39.5	42.5
504070PN	1800	3.7	5.0	40.5	70.5
504252PH	1400	3.7	5.0	42.5	52.5
504468PN	2000	3.7	5.0	44.5	68.5
505048PN	1500	3.7	5.0	50.5	48.5
505068PN	2200	3.7	5.0	50.5	68.5
505075PM	2500	3.7	5.0	50.5	75.5
523040PK	700	3.7	5.2	30.5	40.5
523450PN	1000	3.7	5.2	34.5	50.5
523450PN	1100	3.7	5.2	34.5	50.5
525060PN	2000	3.7	5.2	50.5	60.5
531220PL	100	3.7	5.3	12.5	20.5
551225PH	130	3.7	5.5	12.5	25.5
551430PN	180	3.7	5.5	14.5	30.5
551730PL	300	3.7	5.5	17.5	30.5
551745PH	420	3.7	5.5	17.5	45.5
552025PH	235	3.7	5.5	20.5	25.5
552240PH	400	3.7	5.5	22.5	40.5
552248PN	600	3.7	5.5	22.5	48.5
552566PH	1000	3.7	5.5	25.5	66.5
553030PN	500	3.7	5.5	30.5	30.5
553035PN	600	3.7	5.5	30.5	35.5
553048PT	800	3.7	5.5	30.5	48.5
553248PN	900	3.7	5.5	32.5	48.5
581225PN	140	3.7	5.8	12.5	25.5
585477PN	2600	3.7	5.8	54.5	77.5
601225PL	180	3.7	6.0	12.5	25.5
601259PN	400	3.7	6.0	12.5	59.5
601437PH	230	3.7	6.0	14.5	37.5
601452PN	450	3.7	6.0	14.5	52.5



Yilai Power Technology Co, Ltd

Tel:+86-755-2930 0814 Web:yilaipower.com Email:info@yilaipower.com

Li-ion Polymer Series

Model	Nominal Capacity (mAh)	Nominal Voltage (V)	Max Dimension(mm)		
			Thickness	Width	Length
601529PN	230	3.7	6.0	15.5	29.5
601621PH	150	3.7	6.0	16.5	21.5
601621PN	160	3.7	6.0	16.5	21.5
601624PN	180	3.7	6.0	16.5	24.5
601735PN	350	3.7	6.0	17.5	35.5
601738PN	390	3.7	6.0	17.5	38.5
601750PN	550	3.7	6.0	17.5	50.5
602030PH	300	3.7	6.0	20.5	30.5
602030PN	330	3.7	6.0	20.5	30.5
602040PL	500	3.7	6.0	20.5	42.5
602435PH	400	3.7	6.0	24.5	35.5
602525PN	380	3.7	6.0	25.5	25.5
602535PT	550	3.7	6.0	25.5	35.5
602823PL	350	3.7	6.0	28.5	23.5
603246PH	950	3.7	6.0	32.5	46.5
603448PN	1200	3.7	6.0	34.5	48.5
603450PK	1150	3.7	6.0	34.5	50.5
603943PH	1000	3.7	6.0	39.5	43.5
604545PN	1500	3.7	6.0	45.5	45.5
621432PN	280	3.7	6.2	14.5	32.5
622835PL	680	3.7	6.2	28.5	35.5
623046PN	1000	3.7	6.2	30.5	46.5
632125PL	300	3.7	6.3	21.5	25.5
651447PL	430	3.7	6.5	14.5	47.5
651730PH	260	3.7	6.5	17.5	30.5
652240PL	650	3.7	6.5	22.5	40.5
652263PH	900	3.7	6.5	22.5	63.5
652759PN	1150	3.7	6.5	27.5	59.5
673662PN	1920	3.7	6.7	36.5	62.5
681323PH	155	3.7	6.8	13.5	23.5
681323PH	160	3.7	6.8	13.5	23.5
683333PL	780	3.7	6.8	33.5	33.5
701238PH	280	3.7	7.0	12.5	38.5
701540PN	390	3.7	7.0	15.5	40.5
701840PN	500	3.7	7.0	18.5	40.5



Yilai Power Technology Co, Ltd

Tel:+86-755-2930 0814 Web:yilaipower.com Email:info@yilaipower.com

Li-ion Polymer Series

Model	Nominal Capacity (mAh)	Nominal Voltage (V)	Max Dimension(mm)		
			Thickness	Width	Length
701920PN	200	3.7	7.0	19.5	20.5
702026PN	350	3.7	7.0	20.5	26.5
702028PL	380	3.7	7.0	20.5	28.5
702030PH	350	3.7	7.0	20.5	32.5
702050PN	750	3.7	7.0	20.5	50.5
702174PN	1300	3.7	7.0	21.5	74.5
702260PN	1000	3.7	7.0	22.5	60.5
702425PN	400	3.7	7.0	24.5	25.5
702447PL	900	3.7	7.0	24.5	47.5
702524PN	400	3.7	7.0	25.5	24.5
702540PN	700	3.7	7.0	25.5	40.5
702574PH	1400	3.7	7.0	25.5	74.5
703040PN	920	3.7	7.0	30.5	40.5
704560PL	2700	3.7	7.0	45.5	60.5
722035PH	520	3.7	7.2	20.5	35.5
722060PN	1000	3.7	7.2	20.5	60.5
751535PN	380	3.7	7.5	15.5	35.5
751720PL	210	3.7	7.5	17.5	20.5
752065PH	1100	3.7	7.5	20.5	65.5
752270PN	1300	3.7	7.5	22.5	70.5
781350PH	480	3.7	7.8	13.5	50.5
781920PN	240	3.7	7.8	19.5	20.5
782035PH	500	3.7	7.8	20.5	35.5
782058PH	900	3.7	7.8	20.5	58.5
782525PH	480	3.7	7.8	25.5	25.5
782643PL	1100	3.7	7.8	26.5	43.5
801350PN	500	3.7	8.0	13.5	50.5
801428PL	300	3.7	8.0	14.5	28.5
801723PH	210	3.7	8.0	17.5	23.5
801845PN	600	3.7	8.0	18.5	45.5
802060PN	1200	3.7	8.0	20.5	60.5
802155PN	1000	3.7	8.0	21.5	55.5
802220PN	250	3.7	8.0	22.5	20.5
802526PN	450	3.7	8.0	25.5	26.5
802535PN	720	3.7	8.0	25.5	35.5



Yilai Power Technology Co, Ltd

Tel:+86-755-2930 0814 Web:yilaipower.com Email:info@yilaipower.com

Li-ion Polymer Series

Model	Nominal Capacity (mAh)	Nominal Voltage (V)	Max Dimension(mm)		
			Thickness	Width	Length
802540PN	800	3.7	8.0	25.5	40.5
803040PN	1050	3.7	8.0	30.5	40.5
803448PN	1500	3.7	8.0	34.5	48.5
803944PN	1500	3.7	8.0	39.5	44.5
804045PN	1500	3.7	8.0	40.5	45.5
804565PN	3000	3.7	8.0	45.5	65.5
822937PH	1000	3.7	8.2	29.5	37.5
823048PN	1250	3.7	8.2	30.5	48.5
842445PN	1000	3.7	8.4	24.5	45.5
852033PH	430	3.7	8.5	20.5	33.5
852737PN	850	3.7	8.5	27.5	37.5
882937PL	1100	3.7	8.8	29.5	37.5
901635PN	480	3.7	9.0	16.5	35.5
901849PN	850	3.7	9.0	18.5	49.5
902020PN	300	3.7	9.0	20.5	20.5
902028PN	480	3.7	9.0	20.5	28.5
902050PH	900	3.7	9.0	20.5	50.5
902248PN	1000	3.7	9.0	22.5	48.5
902550PH	1150	3.7	9.0	25.5	50.5
902550PN	1350	3.7	9.0	25.5	50.5
903030PH	650	3.7	9.0	30.5	30.5
903044PN	1400	3.7	9.0	30.5	44.5
903659PN	2400	3.7	9.0	36.5	59.5
922024PN	400	3.7	9.2	20.5	24.5
952270PN	1600	3.7	9.5	22.5	70.5
952653PL	1500	3.7	9.5	26.5	53.5
953058PN	2000	3.7	9.5	30.5	58.5
962831PT	850	3.7	9.6	28.5	31.5
101524PH	300	3.7	10.0	15.5	24.5
102025PH	400	3.7	10.0	20.5	25.5
102065PN	1400	3.7	10.0	20.5	65.5
102540PN	1100	3.7	10.0	25.5	40.5
102540PN	1200	3.7	10.0	25.5	40.5
102765PL	2000	3.7	10.0	27.5	65.5
102930PH	920	3.7	10.0	29.5	30.5



Yilai Power Technology Co, Ltd

Tel:+86-755-2930 0814 Web:yilaipower.com Email:info@yilaipower.com

Li-ion Polymer Series

Model	Nominal Capacity (mAh)	Nominal Voltage (V)	Max Dimension(mm)		
			Thickness	Width	Length
102940PH	1200	3.7	10.0	29.5	40.5
103035PH	1000	3.7	10.0	30.5	35.5
103048PH	1500	3.7	10.0	30.5	48.5
103048PL	1700	3.7	10.0	30.5	48.5
103448PN	2000	3.7	10.0	34.5	48.5
103450PL	1800	3.7	10.0	34.5	50.5
103450PL	2000	3.7	10.0	34.5	50.5
105873PN	5400	3.7	10.0	58.5	73.5
112125PH	500	3.7	11.0	21.5	25.5
112242PN	1100	3.7	11.0	22.5	42.5
112746PH	1500	3.7	11.0	27.5	46.5
122035PN	800	3.7	12.0	20.5	35.5
122535PH	950	3.7	12.0	25.5	35.5
123339PN	1760	3.7	12.0	33.5	39.5
123450PL	2700	3.7	12.0	34.5	50.5
263347PV	500	4.35	2.6	33.5	47.5
302528PV	200	4.35	3.0	25.5	28.5
323058PV	750	4.35	3.2	30.5	58.5
383950PV	1000	4.35	3.8	39.5	50.5
425452PV	1800	4.35	4.2	54.5	52.5
451940PV	400	4.35	4.5	19.5	40.5
502035PV	400	4.35	5.0	20.5	35.5
502072PV	1000	4.35	5.0	20.5	72.5
502236PV	500	4.35	5.0	22.5	36.5
512233PV	450	4.35	5.1	22.5	33.5
521725PV	260	4.35	5.2	17.5	25.5
522540PV	680	4.35	5.2	25.5	40.5
522830PV	560	4.35	5.2	28.5	30.5
531333PV	270	4.35	5.3	13.5	33.5
551525PV	230	4.35	5.5	15.5	25.5
552036PV	450	4.35	5.5	20.5	36.5
552270PV	900	4.35	5.5	22.5	70.5
552531PV	500	4.35	5.5	25.5	31.5
553229PV	650	4.35	5.5	32.5	29.5
562828PV	540	4.35	5.6	28.5	28.5



Yilai Power Technology Co, Ltd

Tel:+86-755-2930 0814 Web:yilaipower.com Email:info@yilaipower.com

Li-ion Polymer Series

Model	Nominal Capacity (mAh)	Nominal Voltage (V)	Max Dimension(mm)		
			Thickness	Width	Length
572330PV	520	4.35	5.7	23.5	30.5
583028PV	650	4.35	5.8	30.5	28.5
601430PV	280	4.35	6.0	14.5	30.5
602525PV	400	4.35	6.0	25.5	25.5
602733PV	780	4.35	6.0	27.5	33.5
643443PV	1250	4.35	6.4	34.5	43.5
751540PV	490	4.35	7.5	15.5	40.5
752440PV	850	4.35	7.5	24.5	40.5
752636PV	900	4.35	7.5	26.5	36.5
842035PV	700	4.35	8.4	20.5	35.5
852055PV	1200	4.35	8.5	20.5	55.5
852831PV	900	4.35	8.5	28.5	31.5
922058PV	1400	4.35	9.2	20.5	58.5
952829PV	900	4.35	9.5	28.5	29.5
123450PV	2850	4.35	12.0	34.5	50.5
342728PS	300	4.4	3.4	27.5	28.5
392323PS	240	4.4	3.9	23.5	23.5
402424PS	260	4.4	4.0	24.5	24.5
454760PS	1900	4.4	4.5	47.5	60.5
462732PS	600	4.4	4.6	27.5	32.5
501923PS	255	4.4	5.0	19.5	23.5
502035PS	350	4.4	5.0	20.5	35.5
502833PS	740	4.4	5.0	28.5	33.5
502834PS	750	4.4	5.0	28.5	34.5
512834PS	780	4.4	5.1	28.5	34.5
552733PS	760	4.4	5.5	27.5	33.5
562833PS	830	4.4	5.6	28.5	33.5
602734PS	850	4.4	6.0	27.5	34.5
632930PS	830	4.4	6.3	29.5	30.5
632931PS	850	4.4	6.3	29.5	31.5
732935PS	950	4.4	7.3	29.5	35.5
752835PS	950	4.4	7.5	28.5	35.5